

# AT-MCRI

## Media Conversion Rack-mount Chassis

### AT-MCRI

Internally powered, rack-mountable chassis, for one unmanaged, standalone Media or Bridging Media Converter

### Overview

The AT-MCRI is a single slot, rack-mountable chassis, capable of housing any of the range of Fast Ethernet and Gigabit Media Converters and Bridging Media Converters. The chassis features an internal power supply, which negates the need to use the external power adapter shipped with the media converter. A front panel LED power indicator shows the user when power is applied to the chassis. All the standalone Media Converters and Bridging Media Converters can be hot inserted and removed from the chassis, thus removing the need to power down the chassis for maintenance and upgrades. The chassis ships with a rack-mount kit.

### Hassle Free Support

All Allied Telesyn AT-MCRI chassis' have a two year warranty and free technical support, ensuring trouble-free installation.

### Technical Specifications

#### Physical Specifications

W x D x H 173mm x 131mm x 44mm  
(6.7" x 5.1" x 1.7")  
Weight 0.800kg (1.77lbs)

#### LED Indicators

1 x Power LED Green (Front Panel)

#### Power Characteristics

Power Adapter Style In line (IEC power inlet)  
Input Voltage 100-240V AC 50/60Hz Auto-sensing  
Output Voltage 12vDC @ 1A

#### Environmental Specifications

Operating Temperature: 0°C to 40°C  
(32°F to 104°F)  
Storage Temperature: -25°C to 70°C  
(-13°F to 158°F)  
Operating Humidity: 5% to 90% non-condensing  
Storage Humidity: 5% to 95% non-condensing  
Maximum Operating Altitude: 3,000 m (10,000 ft.)  
Maximum Storage Altitude: 4,000 m (13,100 ft.)

#### Safety and Electromagnetic

##### Emissions Certifications

EMI: FCC Class A, EN55022 Class A,  
VCCI Class A, C-TICK, CE  
Immunity: EN55024  
Safety: UL60950-1 (CULUS), EN60950-1 (TUV),  
CAN/CSA C22.2 No. 60950-1

#### Package Contents

1 x AT-MCRI Chassis  
4 x Rubber feet for desktop mounting  
2 x Rack-mount Ears (including eight screws)  
1 x Media Converter Carrier  
1 x IEC Power cord (Country specific)  
1 x Installation Guide  
1 x Warranty Registration Card

### Key Features

- One Slot Chassis
- Internal AC Power Supply
- Desktop or Wall-mountable
- Compatible with all standalone Media, and Bridging Media Converters

### Ordering Information

AT-MCRI-xx  
Single slot chassis,

Where xx = 10 US Power Cord  
= 20 European Power Cord  
= 30 UK Power Cord  
= 40 Australian Power Cord

USA Headquarters | 19800 North Creek Parkway | Suite 200 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

[www.alliedtelesyn.com](http://www.alliedtelesyn.com)