



AT-SPLX10

Small Form Pluggable (SFP) Modules

AT-SPLX10

10km 1000LX SFP

Industry Standard

The AT-SP series offers the latest industry standard in flexible, full-duplex Gigabit Ethernet connectivity. These hot-swappable, fiber interfaces simply plug into a SFP slot on Allied Telesyn SFP compatible products. Configurations can be optimised to meet varied distance and service requirements.

Options

The AT-SP series offers short-haul and long-haul solutions. From the inexpensive AT-SPSX to the far-reaching AT-SPZX80, you have the option to extend your network to the distances that meet your performance needs. The CWDM version allows you to take advantage of the CWDM technology in an existing network infrastructure, maximizing fiber efficiency. Multi-rate versions allow technologies other than just Gigabit Ethernet to be transmitted over single mode fiber.

Product Compatibility

The AT-SP series SFPs are compatible with all the Allied Telesyn range of products that support SFP uplink connections.

Technical Specifications

Media Type	SMF
Wavelength	1310nm
Maximum Data Rate	2.125Gbps
Distance	10km
Digital Diagnostics	Yes
Transmit Power (min)	-9.5dBm
Transmit Power (max)	-3dBm

Receive Sensitivity	
at 2.125Gbps (max)	-21dBm
at 1.25Gbps (max)	-22dBm

Power Budget	
at 2.125Gbps (min)	11.5dBm
at 1.25Gbps (min)	12.5dBm

Fiber Connectors: LC

Standard Data Rates Supported

Optical Gigabit Ethernet
 1 x Fiber Channel
 2 x Fiber Channel

Environmental Specifications

Operating Temp	-40°C to 85°C
Operating Humidity	0% to 85% (non condensing)
Storage Temperature	-40°C to 100°C
Storage Humidity	0% to 85% (non condensing)

Key Family Features

- Copper & fiber Solutions
- Connect up to 80km
- Compact size
- Flexible architecture
- Plug-and-play ease of use
- Self-locking mechanism
- 'Coloured' wavelength for CWDM use
- Data: Support for fiber channel and 2X fiber channel
- Telecom: support for OC3/STM-1, OC12/STM-4, & OC48/STM-16
- 2 year warranty

Ordering Information

AT-SPLX10
 10km 1000LX SFP, 9 Micron SMF (1310nm)

USA Headquarters | 19800 North Creek Parkway | Suite 200 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

www.alliedtelesyn.com