



## AT-RPS3004 & AT-PWR3004

### Redundant Power Supply Chassis and Power Module

#### AT-PWR3004

Redundant power supply module (AC supply)

#### AT-RPS3004

Redundant power supply chassis containing one AT-PWR3004 power supply

#### Overview

The Allied Telesis AT-RPS3004 and AT-PWR3004 switch accessories provide optional redundant power options to a range of Allied Telesis switches. Installing a redundant power supply increases network reliability, as the switch can continue to operate in the event of a failure of the switch's main internal power supply, or that of the redundant power supply. Failure of either power supply causes an event to be sent to a Network Management System (NMS) allowing a network administrator to take the appropriate remedial action, thus averting a catastrophic failure on the network.

The AT-RPS3004 is a 19" rack-mountable chassis, capable of holding up to four individual AT-PWR3004 power modules.

Each AT-PWR3004 power module is hot swappable/removable from the AT-RPS3004 chassis, thus increasing system reliability on multi-switch installations.

#### Compatible Switches

AT-8525M  
 AT-8550GB  
 AT-8550SP  
 AT-8516F/SC  
 AT-8624T/2M  
 AT-8648T/2SP

#### Technical Specifications

##### AT-PWR3004

Input voltage	100~240V AC
Power	65W
Dimensions	30.48cm x 10.8cm x 6.35cm (12 x 4.25 x 2.5 in)
Weight	1.06kg (2.35 lb)

##### AT-RPS3004

Dimensions	44cm x 35.56cm x 6.6cm (17.32 x 14 x 2.6 in)
Weight	5.22kg (including 1 x AT-PWR3004)

#### Environmental Specifications

Operating temperature	-20°C to 40°C
Storage temperature	-40°C to 80°C
Relative humidity	<95% non-condensing

#### Key Features

- Provides optional redundant power
- Supplies up to four switches
- Hot swappable modules
- Rack-mountable (kit included)

#### Ordering Information

##### AT-PWR3004

Redundant power supply module (AC supply)

##### AT-RPS3004-xx

Redundant power supply chassis containing one AT-PWR3004 power supply

Where xx =  
 10 for US power cord  
 30 for UK power cord  
 40 for Australian power cord  
 50 for European power cord

USA Headquarters | 19800 North Creek Parkway | Suite 200 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895  
 European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11  
 Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

[www.alliedtelesis.com](http://www.alliedtelesis.com)

© 2007 Allied Telesis Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners.

617-000242 Rev.A