



Rack PDU, Basic, 1U, 16A, 208/230V, (12)C13

APC Basic Rack PDU , Input: 120V, 208V, 230V , Input Connection Type: IEC-320 C20 , Cord Length: 8 feet , Output: 120V, 208V, 230V , Output Connections: IEC 320 C13
Includes: Installation Guide, Rack Mounting Brackets




Part Number : **AP9565**

The most mounting options in the market.

APC offers a wide variety of Basic Rack Power Distribution Units (PDUs), which allow users to distribute power outlets to rack-mount equipment. Horizontal and vertical units are available as well as a variety of power inputs and outputs to fit most power environments. APC now offers Basic Rack PDUs that mount vertically, without tools in the rear channel of a NetShelter VX.

Technical Specifications

Output

Nominal output voltage	120V, 208V, 230V
Maximum Total Current Draw per Phase	16 A
Output Connections	(12) IEC 320 C13 

Input

Nominal input voltage	120V, 208V, 230V
Input frequency	50/60 Hz Hz
Input Connection Type	IEC-320 C20
Cord Length	8.20 feet
Maximum Input Current per phase	16 A
Load Capacity	3680 VA

☐ Physical

Net weight	4.50 lbs. (2.05 kg)
Maximum height	1.75 inches (44 mm)
Maximum width	17.60 inches (447 mm)
Maximum depth	2.25 inches (57 mm)
Shipping Weight	8.00 lbs. (3.64 kg)
Shipping Height	2.75 inches (70 mm)
Shipping Width	18.25 inches (464 mm)
Shipping Depth	9.00 inches (229 mm)
Color	Black

☐ Conformance

Approvals	cUL Listed , CE , UL Listed , VDE
Standard warranty	2 years repair or replace

☐ Environmental

Operating Environment	0 - 45 °C (32 - 113 °F)
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	-25 - 65 °C (-13 - 149 °F)
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-50000 feet (0-15000 meters)