



Rack PDU, Basic, Zero U, 10A,230V, (15)C13



APC Basic Rack PDU , Input: 208V, 230V ,
Input Connection Type: IEC-320 C14 , Cord
Length: 7 feet , Output: 208V, 230V , Output
Connections: IEC 320 C13
Includes: Installation Guide, Rack Mounting
Brackets, Tool less Mounting Kit


Part Number : **AP9568**

The most mounting options in the market.

APC offers a wide variety of Basic Rack Power Distribution Units (PDUs), which allow users to distribute power outlets to rack-mount equipment. Horizontal and vertical units are available as well as a variety of power inputs and outputs to fit most power environments. APC now offers Basic Rack PDUs that mount vertically, without tools in the rear channel of a NetShelter VX.

Technical Specifications

Output

Nominal output voltage	208V, 230V
Maximum Total Current Draw per Phase	10 A
Output Connections	(15) IEC 320 C13 

Input

Nominal input voltage	208V, 230V
Input frequency	50/60 Hz Hz
Input Connection Type	IEC-320 C14
Cord Length	6.50 feet
Acceptable Input Voltage	200-240 VAC
Maximum Input Current per phase	10 A
Load Capacity	2300 VA

Physical

Net weight	4.40 lbs. (2.00 kg)
Maximum height	24.00 inches (610 mm)
Maximum width	1.75 inches (44 mm)
Maximum depth	1.75 inches (44 mm)
Shipping Weight	6.00 lbs. (2.73 kg)
Shipping Height	25.50 inches (648 mm)
Shipping Width	7.00 inches (178 mm)
Shipping Depth	6.00 inches (152 mm)
Color	Black

Conformance

Approvals	cUL Listed , CE , UL Listed , VDE
Standard warranty	2 years repair or replace

Environmental

Operating Environment	0 - 45 °C (32 - 113 °F)
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	-25 - 65 °C (-13 - 149 °F)
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-50000 feet (0-15000 meters)