



Rack PDU, Basic, ZeroU, 16A, 230V, (20)C13 & (4)C19; IEC C20

APC Basic Rack PDU , Input: 230V , Input Connection Type: IEC-320 C20 , Cord Length: 10 feet , Output: 230V , Output Connections: IEC 320 C13, IEC 320 C19
Includes: Installation Guide, Tool less Mounting Kit

Part Number : **AP7552**




The most mounting options in the market.

APC offers a wide variety of Basic Rack Power Distribution Units (PDUs), which allow users to distribute power outlets to rack-mount equipment. Horizontal and vertical units are available as well as a variety of power inputs and outputs to fit most power environments. APC now offers Basic Rack PDUs that mount vertically, without tools in the rear channel of a NetShelter VX.

Technical Specifications

Output

Nominal output voltage	230V
Maximum Total Current Draw per Phase	16 A
Output Connections	(20) IEC 320 C13  (4) IEC 320 C19

Input

Nominal input voltage	230V
Input frequency	50/60 Hz Hz
Input Connection Type	IEC-320 C20
Cord Length	10 feet
Maximum Input Current per phase	16 A
Load Capacity	3680 VA

Physical

Net weight	10.70 lbs. (4.86 kg)
Maximum height	63.75 inches (1619 mm)
Maximum width	2.20 inches (56 mm)
Maximum depth	1.73 inches (44 mm)
Shipping Weight	12.70 lbs. (5.77 kg)
Shipping Height	84.00 inches (2134 mm)
Shipping Width	6.00 inches (152 mm)
Shipping Depth	5.00 inches (127 mm)
Color	Black

Conformance

Approvals	CE , EN 60950 , VDE
Standard warranty	2 years repair or replace

Environmental

Operating Environment	0 - 45 °C (32 - 113 °F)
Operating Relative Humidity	5 - 95 %
Operating Elevation	0-10000 feet (-3000 meters)
Storage Temperature	-25 - 65 °C (-13 - 149 °F)
Storage Relative Humidity	5 - 95 %
Storage Elevation	0-50000 feet (0-15000 meters)