



Rack PDU, Switched, Zero U, 16A, 230V, (21)C13&(3)C19

APC Switched Rack PDU , Input: 230V , Input Connection Type: IEC 309 , Cord Length: 3 feet (91.44 cm) , Output: 230V , Output Connections: IEC 320 C13,IEC 320 C19

Includes: Installation Guide, Rack Mounting Brackets, Toolless Mounting Kit, User Manual

Part Number : **AP7951**




The most mounting options in the market.

APC offers a wide variety of Basic Rack Power Distribution Units (PDUs), which allow users to distribute power outlets to rack-mount equipment. Horizontal and vertical units are available as well as a variety of power inputs and outputs to fit most power environments. APC now offers Basic Rack PDUs that mount vertically, without tools in the rear channel of a NetShelter VX.

Technical Specifications

Output

Nominal output voltage	230V
Maximum Total Current Draw per Phase	16 A
Output Connections	(21) IEC 320 C13  (3) IEC 320 C19

Input

Nominal input voltage	230V
Input frequency	50/60 Hz Hz
Input Connection Type	IEC 309
Cord Length	3 feet (91.44 cm)
Acceptable Input Voltage	200-250 VAC
Maximum Input Current per phase	16 A
Load Capacity	3680 VA

Physical

Net weight	13.00 lbs. (5.91 kg)
Maximum height	63.75 inches (1619 mm)
Maximum width	2.19 inches (56 mm)
Maximum depth	1.73 inches (44 mm)
Shipping Weight	15.00 lbs. (6.82 kg)
Shipping Height	84.00 inches (2134 mm)
Shipping Width	6.00 inches (152 mm)
Shipping Depth	5.00 inches (127 mm)
Color	Black

Environmental

Operating Environment	0 - 45 °C (32 - 113 °F)
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	-25 - 65 °C (-13 - 149 °F)
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-50000 feet (0-15000 meters)

Conformance

Approvals	AS/NZS 3548 (C-Tick) Class A , CE , EN 55022 Class A , EN 55024 , EN 60950 , IEC 61000-3-2 , IEC 61000-3-3 , VDE
Standard warranty	2 years repair or replace