



Blank covers in black and white, for Keystone openings in Patch Panels



unilan® Patch Panel KS 24x - shielded

Product information

unilan® Patch Panel KS 24x shielded

Application

Shielded patch panel to be used with up to 24 Modules with Keystone fitting.

For the modules PS-GG45 7A is recommended the Patch Panel MGK 24x with front made of stainless steel.
Snap in modules are easily fitted into the patch panel.
Unused ports can be covered with blanking elements.

Description

Front cover made of flame retardant compound, UL94V-0 rated in combination with stainless steel and a cable strain relief.
Frontview in grey, similar to RAL 7035 or in black, similar to RAL 9005.
Modules are not part of the delivery.
Strain relief with cable ties.

Suitable for the following unilan® Modules:

- PS-GG45 7A 1000 MHz 4P shielded (Patch Panel MGK 24x)
- RJ45 Modul KS-T 1/8 Tool-Less shielded

Dimensions

Width	482 mm (19")
Depth	160 mm (including cable strain relief)
Height	44 mm (1U)

Article No.	Description	Colour (similar)	PU
418 019	unilan® Patch Panel KS 24x, 19" 1U , for 24x RJ45-Keystone Modules (FTP) (delivered without modules)	black RAL 9005	1 piece
418 020	unilan® Patch Panel KS 24x, 19" 1U , for 24x RJ45-Keystone Modules (FTP) (delivered without modules)	grey RAL 7035	1 piece
440 042	unilan® Patch PanelMGK 24x, 19" 1U , for 24x RJ45-Keystone Modules (FTP) (delivered without modules) specially for PS-GG45 7A Modules	stainless steel	1 piece

Article No.	Accessories/Description	Colour (similar)	PU
418 010	Blank cover for Keystone Openings	white	10 pieces
418 011	Blank cover for Keystone Openings	black	10 pieces
418 060	unilan® Module KS-T 6A 1/8 Tool-less Cat. 6A/E _A shielded	metall	10 pieces
418 053	unilan® Module KS-T 1/8 Tool-less Cat. 6/E _A shielded	metallic	10 pieces
418 055	unilan® Module KS-T5 1/8 Tool-less Cat. 5e shielded	metallic	10 pieces
400 100	unilan® Module PS-GG45 7A 1000 MHz 4P shielded	metallic	1 piece