

Breakout Solutions

Breakout Box



NO12SABB6D-A



NO4SABB4D-A





opticalICON Breakout Box

- Breakout boxes are used to split multichannel connections as the opticalICON QUAD and MTP® to either dual or single channels
- Dust and waterproof according to IP67 in mated condition

Breakout Box

| | |
|---------------------------|--|
| NO4SBB2D-A ¹⁾ | 1 x NO4FDW-A to 2 x NO2-4FDW-A, Singlemode PC |
| NO4SABB2D-A ¹⁾ | 1 x NO4FDW-A to 2 x NO2-4FDW-A, Singlemode APC |
| NO4MBB2D-A ¹⁾ | 1 x NO4FDW-A to 2 x NO2-4FDW-A, Multimode PC |
| NO4SBB4D-A | 1 x NO4FDW-A to 4 x NO2-4FDW-A, Singlemode PC |
| NO4SABB4D-A | 1 x NO4FDW-A to 4 x NO2-4FDW-A, Singlemode APC |
| NO4MBB4D-A | 1 x NO4FDW-A to 4 x NO2-4FDW-A, Multimode PC |



| | |
|--------------|--|
| NO12SABB6D-A | 1 x NO12FDW-A to 6 x NO2-4FDW-A, Singlemode APC (MTP® connector) |
| NO12MBB6D-A | 1 x NO12FDW-A to 6 x NO2-4FDW-A, Multimode PC |
| NO12SABB3Q-A | 1 x NO12FDW-A to 3 x NO4FDW-A, Singlemode APC (MTP® connector) |
| NO12MBB3Q-A | 1 x NO12FDW-A to 3 x NO4FDW-A, Multimode PC |

