

ARMOURLUX LUMINA®

ArmourLux LUMINA® 2/4 Channel Junior HMA Plug to Plug assembly is our premium option for fibre optics in harsh environments. Utilising Expanded Beam technology, the connector is rugged, can be easily cleaned and being hermaphroditic, is simple and easy to connect.

Our ArmourLux LUMINA® systems are assembled in-house at our dedicated UK based, production facility. The range has been developed over the years to deliver class leading optical performance. It is fully interoperable with other HMA Junior products from TE, Stratos, DiGiCo and others.

We use a cable based on MIL-C-85045 Military Standard for the ArmourLux series, which is extremely strong, lightweight and rugged. It's ideal for harsh environments, striking a balance between durability and portability. It has a high crush resistance yet remains flexible so its easy to deploy and retrieve. The LUMINA® expanded beam connectors in a 2 or 4 channel fibre are ideal for multimode and singlemode field deployable, harsh environment applications.



ARMOURLUX
COMMUNICATE PROTECT DELIVER

LUMINA®



MILITARY GRADE CONNECTOR

Military grade LUMINA® connector designed to meet MIL83526 / MIL20/ MIL21.



RUGGED, BEND INSENSITIVE FIBRE

Flexible, bend insensitive tactical fibre designed for harsh environments.



MANUFACTURED IN THE UK

Products are manufactured in the UK and individually serialised for traceability.



HERMAPHRODITIC CONNECTORS

For daisy-chaining.



EASY CLEAN & CONNECT

Lens technology allows for easy clean and connect.

Applications

Our ArmourLux LUMINA® assemblies are suitable for use in a wide range of applications including, but not limited to:

- Harsh environments
- Outdoor broadcast
- Challenging, remote conditions



Technical Specification



LUMINA® Plug



LUMINA® Jam Nut Bulkhead - Strain Relief



LUMINA® Square Flange Bulkhead - Strain Relief

Technical Specification


| | | |
|-----------------------|---|--|
| Optical Loss | Multimode (50/125 at 850/1300nm) Singlemode (9/125 at 1310/1550nm) | 0.8dB typical (1.0dB max) 1.0dB typical (1.5dB max) |
| Return Loss | Multimode (50/125 at 850/1300nm) Singlemode (9/125 at 1310/1550nm) | >23dB >32dB |
| Operating Temperature | -40 to +70°C | |
| Storage Temperature | -55 to +85°C | |
| Water Immersion | 15m for 24 hours | |
| Vibration Sinusoidal | 10-500Hz 0.75 amplitude @10g | |
| Drop | 1.2m x 500 off | |
| Bump | 4000 bumps @ 30g | |
| Durability | x3000 matings | |
| Tensile | 2000N cable dependent | |

Reel Capacity


| Reel Type | 2 Channel | 4 Channel |
|-----------|-----------|-----------|
| R2 | 141m | 123m |
| R3 | 277m | 241m |
| R9 | 447m | 390m |
| R10 | 710m | 618m |
| R6 | 906m | 847m |
| R7 | 1359m | 1270m |

Technical Drawings


LUMINA® Connector




LUMINA® Square Flange Bulkhead



LUMINA® Jam Nut D Bulkhead



Optical Insert Arrangements



Buy with Confidence

All assemblies are made in the UK. We are an ISO14001 and ISO9001 accredited company, where Quality and Customer Service are our highest priorities.

We're here to support you - whatever the question about fibre, we will help you!



Cable Assembly Part Number Configurator

LJ **2** **1** **A** **P1** **A** - **R2** - **250** - **T** **A1** **B**

Connector Style
LJ: LUMINA Junior
LM: LUMINA Mini
LS: LUMINA Senior

Fibre Count
2: 2 Fibre Channels
4: 4 Fibre Channels

Fibre Mode
1: OM1 62.5/125 Multimode
3: OM3 50/125 Multimode
9: OS2 9/125 Singlemode
4: OM4 50/125 Multimode

Wavelength
A: 850/1300nm Multimode
B: 1310/1550nm Singlemode
C: 850nm Multimode
D: 1300nm Multimode
E: 1310nm Singlemode
F: 1550nm Singlemode

End A
P1: Plug
B1: Jam Nut D Bulkhead (Non-Conductive)
B2: Square Flange Bulkhead (Non-Conductive)
B1C: Jam Nut D Bulkhead (Conductive)
B2C: Square Flange Bulkhead (Conductive)

End B
A: Same as End A
3: ST Connector
4: LC Connector
5: SC Connector
8: FC Connector
9: Bare End

Shell Colour
B: Black
O: Olive Green
BR: Bronze
S: Silver

Shell Material
A1: Aluminium Hard Anodised (Black) - Non Conductive (Bulkhead)
A2: Aluminium Hard Anodised (Black) - Conductive (Plug)
N: Nickel Aluminium Bronze (NAB)
S: Stainless Steel

Cable Type
T: Tactical
Z: 3mm Zipped
MZ: 1.8mm Zipped

Length
Example
1.5 = 1.5m
250 = 250m

Reel Type
R2: GT310 Polycarbonate Rubber
R3: GT380 Polycarbonate Rubber
R6: SK4812
R7: SK4813
R9: HT385
R10: HT485
0: No Reel

Note: Options in red are available on request.

Please contact us for more information by calling **01488 685800**.

Why Choose Universal Networks?

Universal Networks are JOSCAR, Cyber Essentials ISO14001 and ISO9001 accredited, fibre deployable experts specialising in the design and delivery of custom made, rugged fibre solutions suitable for harsh environments. With over 30 years of experience, we have worked with a variety of companies operating in some of the most challenging conditions, including both the MOD and affiliated companies to the defence industry.

We manufacture in the UK where possible and deploy worldwide. We are passionate about finding the right solution for your requirements, so our knowledgeable team focus on understanding your project to ensure they recommend and supply the right product for your job. With a strong focus on customer service, along with in-house capabilities to manufacture and repair your cables, we are here to offer expert advice and guidance every step of the way.



Certificate Number 15035



For more information, visit us online at:

www.universalnetworks.com

or call us on:

01488 685800



LUMINA®

ARMOURLUX
COMMUNICATE PROTECT DELIVER

ArmourLux is a brand of Universal Networks UK Limited.
Charnham Lane, Hungerford, Berkshire RG17 0EY.
T: +44 (0) 1488 685800 | www.universalnetworks.com