



Industry Standard Connectors

The ArmourLux300 LC-MAX Lite is compatible with standard LC sockets and is protected in an IP68 rated housing.



100% compatible LC



Highest quality engineering



IP68 Cap & Tether

Capacity per Reel (m)

	2	4	
Number of Fibres	2	4	
Cable Diameter	3.4mm	4.0mm	
REEL OPTION	R1	207m	150m
	R2	384m	277m
	R3	750m	542m
	R9	1206m	871m
	R10	1925m	1391m
	R6	2637m	1905m
	R7	3955m	2857m

Cable Comparison

	2	4	
Number of Fibres	2	4	
Cable Diameter	3.4mm	4.0mm	
SPECIFICATION	Weight/km	12kg	14kg
	Tensile Strength Short Term	1000N	
	Operating Temperature	-70°C to +85°C	
	Crush Long/Short Term	3000N/m / 5000N/m (IEC 60794-2-20)	

Features

- Rugged, metal bodied LC connector
- Mates directly with standard LC socket
- ABS Polymer shell protects from dust and water
- Snag-free protective cap
- Quality mini tactical fibre cable
- Excellent cable retention
- 2 & 4 core, bend insensitive fibre
- Available in both multi and singlemode
- Compact, high capacity reels
- Lightweight and easy to carry
- Manufactured in the UK
- Aftersales refurbish and repair service

To see our other range ArmourLux cable ranges, to request an ArmourLux sample or for more information, please call: **01488 685 800** or email: info@armourlux.com



ArmourLux is a brand of Universal Networks UK Limited
 Charnham Lane, Hungerford, Berkshire RG17 0EY.
 T: +44 (0) 1488 685800 | www.armourlux.com

