ArmourLux500

E C T

The Right Solution

ARMOURLUX

iPPRO

COMMUNI

ArmourLux500 meets the demands of mobile fibre optic communication, for media, audio, security, data...and more. Despite the variety of uses the requirements are often similar - a re-usable fibre cable that is easy to deploy, retrieve, connect, transport and store, over and over again. ArmourLux500 addresses all of these needs.

So what's Unique about ArmourLux500 iPPRO

DELIV

500

 \odot

XII

° 11

A competitively priced, high fibre density - up to 24 fibres - per connector with Tactical deployable fibre, where high cable retention and durability are important. When mated the connector is locked and offers IP68 protection to keep out water and dust. You can hook up to a bulkhead or a fanout cable to convert to standard connectors if preferred. The Military grade Tactical fibre manufactured by Belden & OCC is durable and suited to repeated retrieval and deployment.

Buy with Confidence

All ArmourLux assemblies are made in the UK. We're also an ISO9001 accredited company, where quality and customer service are our highest priorities. With over 25 years experience as a trusted provider of fibre optic cables, you can be reassured we understand the requirements of mobile fibre optic communications.



Hest Selice MO 7 Fibre ray port Parger Patrie









The ipprover Connector

Available in 2, 12 and 24-fibre connectors, we also offer a 4 fibre option using two IP-PRO2 plugs.







IP-PRO 2

IP-PRO 12/24

IP68 Cap & Tether

Capacity per Reel (m)

Number of Fibres	2	4	8	12	24
Cable Diameter	5.4mm	5.8mm	6.4mm	7.3mm	8.5mm
R1	76m	67m	49m	36m	33m
R2	141m	123m	90m	66m	61m
R3 R9	277m	241m	177m	129m	120m
	447 m	390m	286m	209m	194m
R10	710m	618m	454m	331m	308m
RG	906m	847 m	622m	453m	422m
R7	1359m	1270m	933m	680m	633m

Cable Comparison

Number of Fibres	2	4	8	12	24		
Cable Diameter	5.4mm	5.8mm	6.4mm	7.3mm	8.5mm		
Weight/km	26kg	30kg	37 kg	45kg	55kg		
Tensile Strength Short Term Operating Temperature	300N	400N	400N	450N	450N		
Operating Temperature	-55°C to +85°C						
Crush Long/Short Term	3000N/m / 5000N/m (IEC 60994-2-20)						

Features

- 2, 12 and 24 fibres per connector
- IP68 protected from dust and water
- Quality Belden Tactical fibre cable
- Compact, high capacity reels
- Made from lightweight PBT
- Range of IP68 chassis connectors
- Available in both multi and single mode
- Snag-free protective cap
- Excellent cable retention
- Lightweight and easy to carry
- Manufactured in the UK
- Aftersales refurbish and repair service

500

To see our other range ArmourLux cable ranges, to request an ArmourLux sample or for more information, please call: 01488 685 800 or email: info@armourlux.com

COMMUNICATE PROTECT DELIVER

ArmourLux is a brand of Universal Networks UK Limited Charnham Lane, Hungerford, Berkshire RG17 0EY. T: +44 (0) 1488 685800 | F: +44 (0) 1488 685899 | www.armourlux.com

© Copyright 2023 Universal Networks UK Ltd. Version 2.0.